





TRANCHEUR CARACTÉRISTIQUE TECHNIQUE



UNI 350

	350 G	350 G PLUS	350 G COMFORT	350 GA	350 C
Diamètre Lame (mm)	350	350	350	350	350
Moteur	0,5 hp - 0,37 kw	0,5 hp - 0,37 kw	0,5 hp - 0,37 kw	0,5 hp - 0,37 kw	0,5 hp - 0,37 kw
Anneau de Protection Fixe	√	√	√	√	√
Commande Basse Tension	√	√	√	√	√
Sécurité Blocage Chariot	√	√	√	√	√
Etanchéité Moteur	IP 54	IP 54	IP 54	IP 54	IP 54
Norme	uni 1974	uni 1974	uni 1974	uni 1974	uni 1974
CAPACITÉ DE COUPE - mm					
Rectangle 	300 x 155	300 x 155	300 x 155	300 x 155	320 x 265
Carré 	200 x 200	200 x 180	200 x 200	200 x 200	265 x 265
Rond 	Ø 235	Ø 200	Ø 235	Ø 235	Ø 265
Épaisseur maximale 	25	25	25	25	20
VITESSE DE COUPE			xé 40	variable de 15 à 50	
DIMENSIONS - mm					
Empattement	450 x 590	450 x 590	450 x 590	450 x 590	450 x 590
Largeur Totale	627	662	662	662	718
Profondeur Totale	739	800	800	800	800
Hauteur Totale	560	614	719	688	565
Poids Net	38 kg	41 kg	55 kg	55 kg	42 Kg
Poids Brut	40 kg	46 kg	60 kg	60 kg	47 Kg
Dimensions d'Emballage - cm	82 x 77 x 75 ht	82 x 77 x 75 ht	83 x 77 x 86 ht	83 x 77 x 86 ht	82 x 77 x 75 ht