

TRANCHEUR CARACTÉRISTIQUE TECHNIQUE



9300

	9300 G	9300 G PLUS	9300 G COMFORT	9300 GA	9300 S
Diamètre Lame (mm)	300	300	300	300	300
Moteur	0,33 hp - 0,24 kw	0,33 hp - 0,24 kw			
Anneau de Protection Fixe	√	√	√	√	√
Commande Basse Tension	√	√	√	√	√
Sécurité Blocage Chariot	√	√	√	√	√
Étanchéité Moteur	IP 54	IP 54	IP 54	IP 54	IP 54
Norme	uni 1974	uni 1974	uni 1974	uni 1974	uni 1974
CAPACITÉ DE COUPE - mm					
Rectangle 	220 X 180	220 X 180	220 X 180	220 X 180	220 X 180
Carré 	180 x 180	180 x 180	180 x 180	180 x 180	190 x 190
Rond 	Ø 200	Ø 200	Ø 200	Ø 200	Ø 200
Épaisseur maximale 	15	15	15	15	15
VITESSE DE COUPE			xé 40	variable de 15 à 50	
DIMENSIONS - mm					
Empattement	375 x 500	375 x 500	375 x 500	375 x 500	375 x 500
Largeur Totale	577	577	577	577	528
Profondeur Totale	684	684	684	684	689
Hauteur Totale	434	534	629	534	488
Poids Net	33 kg	33 kg	44 kg	43 kg	31 kg
Poids Brut	37 kg	37 kg	47 kg	46 kg	35 kg
Dimensions d'Emballage - cm	61 x 71 x 65 ht	61 x 71 x 65 ht	74 x 72 x 83 ht	74 x 72 x 83 ht	61 x 71 x 65 ht